ERO1BEM Pro

Mesh Extender

BE18100 Tri-Band WiFi7









Main Chipset

BCM6766

WiFi 7

2.4G 4X4

5G 4X4

6G 4X4

Easy Mesh R4

Mesh Backhaul and Topology

WiFi 6Ghz

LAN 10GE

Daisy Chain

Star topology

OpenSync ready

(6.2 in roadmap)



Product Specifications



Wireless Standard 802.11 a/b/g/n/ac/ax/be

Wireless Signal Rates Up to 18.1 Gbps

2.4GHz Band 2x2 11be up to 700 Mbps 5GHz Band 4x4 11be up to 5.8 Gbps 6GHz Band 4x4 11be up to 11.6 Gbps

Multi link operation Concurrent operation of 6G+5G+2.4G

Operating Mode Auto by default

Wireless Communication Enable

Wireless Security WPA, WPA2 and WPA3

Auto channel selection Supported
Single SSID Supported

Steering Band & Client steering

Security Enabled
SSID Broadcast Control Enabled
Transmission speed Wireless Auto

Matter Supported (Optional) BLE + Zigbee + Thread

Supported

Network Features.

QoS Traffic Control (IP)

Café-style guest network

DNS Relay

EasyMesh Rel5

PPPoE, DHCP, static IP WAN connectivity on connectivity DHCP by default NAT Supported MultiRangePort Forwarding Supported Virtual server, special Application & DMZ host **DHCP Server** Supported UPnP, DDNS Supported MAC Address Cloning Supported **IGMP Snoop** Supported



Supported

Supported

Supported



NAT for basic firewall support Supported
Packet filtering firewall Supported
Password authentication to gateway Supported



Configuration download / upload Supported
Telnet / SSH Supported
SNTP Supported
Remote & Web management Supported
Self-Healing Supported
TR-069 / TR-181 Supported
Echo mode (wireless switch schedule) Supported



Interface WAN port, Ethernet, Power

Power Supply 12V 2.5A DC

Button Reset, Power On/Off, WPS,

WiFi On/Off

Dimension 160mm x 178mm x 74mm

Operating Temperature 0° C ~ 40° C

Operating Humidity 10% ~ 90%, noncondensing

Storage Temperature -20° C ~ 70° C

Storage Humidity 5% ~ 90%, noncondensing



Smart Led.

Red Boot or No Internet Access

Red Blinking WiFi Backhaul fail

Blue Ready to install
White Internet access

Green Low WiFi Connectivity

Quality

Interface.





